

LIQUID DEFOAMER

Anti Foaming Agent



TREATMENT

Liquid Defoamer is a fast acting defoaming agent for use in the recovery tank of extractors. It reduces foaming, keeping vacuums operating at top performance.

- Easy to use formulation
- Controls foaming in recovery tanks
- Available in: 1 L (34 oz), 4 L (1.06 US gal), 20 L (5.28 US gal) or 205 L (54.1 US gal)

KEEP FOAMING UNDER CONTROL WITH LIQUID DEFOAMER

DIRECTIONS FOR USE:

Shake well before using.

Liquid Defoamer can be used at full strength or diluted 8 oz (236 ml) per gallon (3.78 L) 1:15 dilution depending on foaming conditions.



Diluted pH: 10.6
Dilution Ratio: Up to 1:15

Liquid Defoamer can be poured directly into the recovery tank, or into the vacuum hose, to control foaming from residues left in carpets from previous shampooing.

NOTE: Do not mix Esteam Liquid Defoamer with any other chemical product.

Keep this product out of reach of children. Read the Material Safety Data Sheet and Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.

www.esteam.com



1-800-653-8338

See Material Safety Data Sheet at www.esteam.com/msds.php