TUFT GUARD II

Fluorochemical Carpet Protector





Tuft Guard II is an advanced water based carpet protector using the latest in environmentally conscious fluorochemical technology, Tuft Guard II delivers superior performance for dry and oily soil resistance, with the benefit of added acid stain blockers carpet fibres are protected from absorbing acid based stains. This product allows for easier spot and spill clean up while at the same time reducing excess fibre wear by protecting carpet from abrasive soils resulting in extended carpet life.

- **Enhanced performance**
- **Acid stain blockers**
- **Contains New advanced fluorochemical protectors**
- Protects against oily and dry soils
- Mild scent
- **VOC** compliant
- **Environmentally preferable**
- Meets specifications for use on stain resistant carpets
- Available in: 4 L (1.06 US gal.) or 20 L (5.28 US gal.)

PREVENT STAINS FROM PENETRATING CARPET FIBRES

DIRECTIONS FOR USE:

Pretest in an inconspicuous location for color fastness and fibre

Ensure equipment used for applying mixed solution is thoroughly cleaned out.

For damp cleaned carpet: Mix 25½ oz (754 ml) of Tuft Guard II with I gal (3.78 L) of water. (1:4 Dilution)

For clean dry carpet: Mix 14 oz (413 ml) of Tuft Guard II

with I gal (3.78 L) of water. (1:8 Dilution)



Diluted pH: 5.8 Dilution Ratio: 1:4 - 1:8

Apply mixed solution using a pump-up or power sprayer, spraying evenly over carpet. Then immediately spray a second application at right angles to first pass. One gallon (3.78 L) of mixed solution for damp carpet will cover 200 square feet (18.6 m2). One gallon (3.78 L) of mixed solution for dry carpets will cover 100 square feet (9.3 m2). Allow treated carpet to dry before being put back in use.

NOTE: Do not mix Esteam Tuft Guard II with any other chemical product. Do not spray onto hard surface floors or walls. Immediately wipe off overspray with a damp cloth.

Keep this product out of reach of children. Read the Material Safety Data Sheet and Product Label before using. Take the necessary precautions dictated by the label to ensure that your health and that of your customers' is protected.



www.esteam.com

1-800-653-8338